## LISTING AND AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

 (Currently amended) A method <u>executed by a decoder</u> for automatically modeling film grain patterns <u>for insertion in a video sequence</u>, comprising the steps of:

transforming a set of film grain samples to the frequency domain;

storing each set of coefficients resulting from such transform, the coefficients forming a pattern;

analyzing the pattern created by the transform coefficients; and estimating the cut frequencies of a 2D band-pass filter that can effectively simulate the pattern of transform coefficients by filtering random noise in a frequency domain.

- (Original) The method according to claim 1 further comprising the step of transmitting at least one cut frequency in a Supplemental Enhancement Information message.
- (Original) The method according to claim 1 wherein the film grain samples are processed in blocks of N x N pixels.
- 4. (Original) The method according to claim 3 wherein the step of analyzing the pattern created by the transform coefficients further comprises the steps of:

computing a mean block of N  $_{X}$  N transform coefficients by averaging the transform coefficients from all the stored blocks;

defining horizontal and vertical mean vectors of N components each by averaging the mean block of N  $\times$  N coefficients along rows and columns, respectively, of each transformed block:

representing the horizontal and vertical mean vectors as separate curves; and establishing horizontal and vertical cut frequencies from the curves represented by the horizontal and vertical mean vectors, respectively.

(Original) The method according to claim 4 further comprising the step of low pass filtering at least one mean vector. 
 Serial No. 10/569,318
 PU030259

 Art Unit 2624
 Customer No. 24498

(Original) The method according to claim 4 wherein the at least one cut frequency is established from an intersection point in the curve representing the mean vector.

- (Original) The method according to claim 4 wherein each of a low and a high cut frequency is established from a first and second intersection points in the curve representing the mean vector.
- (Original) The method according to claim 3 wherein the step of analyzing the pattern created by the transform coefficients further comprises the steps of:

computing a mean block of N x N transform coefficients by averaging the transform coefficients from all the stored blocks:

defining horizontal and vertical mean vectors of N components each by averaging the mean block of  $N \times N$  transform coefficients along rows and columns, respectively, of each transformed block; averaging the horizontal and vertical mean vectors into a single mean vector;

representing the mean vectors as a curve; and establishing horizontal and vertical cut frequencies from the curve represented by the mean vector.

- (Original) The method according to claim 8 further comprising the step of low pass filtering the mean vector.
- (Original) The method according to claim 8 wherein at least one cut frequency is established from an intersection point in the curve representing the mean vector.
- (Original) The method according to claim 8 wherein each of a low and a high cut frequency is established from a first and second intersection points in the curve representing the mean vector.
- (Currently amended) A method executed by a decoder for automatically modeling film grain patterns for insertion in a video sequence, comprising the steps of:

receiving a set of film grain samples performing a transform on the set of film grain samples to the frequency domain;

storing each set of coefficients resulting from such transform, the coefficients forming a pattern;

Serial No. 10/569,318 Art Unit 2624 PU030259 Customer No. 24498

analyzing the pattern created by the transform coefficients; and estimating the cut frequencies of a 2D band-pass filter that can effectively simulate the pattern of transform coefficients by filtering random noise in a frequency domain.